ISO Size Type Code: 45G0, 45G1



- Suitable for voluminous cargo up to max. 2.70 m (8' 101/4") height
- Various lashing devices with a permissible load of 1,000 kg (2,205 lbs) each on the top and bottom longitudinal rails and the corner posts
- Lashing rings on each top longitudinal rail, particularly suitable for the transport of hanging garment equipment
- Majority of containers tested and certified for ONE-DOOR-OFF OPERATION, but then with limited stack weight
- Floor height 170 mm (ground level to interior floor surface, tolerance deviation possible)
- Consider over-height for inland transportation (e.g. bridges, clearances, tunnels etc.)

	Inside dimensions		Door openings		Weights			Capacity	
9' 6" high	Length	Width	Height	Width	Height	Max. gross	Tare	Max. payload	
	mm	mm	mm	mm	mm	kg	kg	kg	m³
	ft	ft	ft	ft	ft	lbs	lbs	lbs	ft ³
Wooden floor	12,032	2,432	2,700	2,340	2,597	32,500	3,850	28,650	76.3
Steel container with	39' 55/8"	7' 11¾"	8' 101/4"	7' 81/8"	8' 61/4"	71,650	8,488	63,162	2,695
corrugated walls		2,352					3,900	28,600	
		7' 85/8"					8,598	63,052	
		2,342							
		7' 81/8"							

Hapag-Lloyd serial number excerpt						
HLBU	106300-109299					
HLBU	114900-116524					
HLBU	141100-144399					
HLBU	147300-149799					
HLBU	128700-133499					
HLXU	823250-824749					

	Inside dimensions			Door openings		Weights			Capacity
9' 6" high	Length	Width	Height	Width	Height	Max.	Tare	Max.	
						gross		payload	
	mm	mm	mm	mm	mm	kg	kg	kg	m ³
	ft	ft	ft	ft	ft	lbs	lbs	lbs	ft ³
Steel floor	12,032	2,352	2,700	2,340	2,597	32,500	4,300	28,200	76.4
Steel container with	39' 55/8"	7' 85/8"	8' 101/4"	7' 81/8"	8' 61/4"	71,650	9,480	62,170	2,698
corrugated walls		2,342					3,950	28,550	76.3
		7' 81/8"					8,708	63,603	2,695
							3,830	28,670	
							8,444	63,206	

Hapag-Lloyd serial number excerpt						
HLXU	655900-655999					
HLBU	174950-175149					
HLBU	127700-128699					

For further information about the steel-floor container, please see page 32.