ISO Size Type Code: L5G0, L5G1



- Suitable for voluminous cargo up to max. 2.70 m (8' 101/4") height
- Units built with corner castings at 40 ft and 45 ft positions
- Various lashing devices with a permissible load of 1,000 kg (2,205 lbs) each on the top and bottom longitudinal rails and the corner posts
- Floor height 170 mm (ground level to interior floor surface, tolerance deviation possible)
- Consider over-height for inland transportation (e.g. bridges, clearances, tunnels etc.)

	Inside dimensions			Door openings		Weights			Capacity
9' 6" high	Length	Width	Height	Width	Height	Max. gross	Tare	Max. payload	
	mm	mm	mm	mm	mm	kg	kg	kg	m <sup>3</sup>
	ft	ft	ft	ft	ft	lbs	lbs	lbs	ft <sup>3</sup>
Wooden floor	13,556	2,352	2,700	2,340	2,597	32,500	4,700	27,800	86.0
Steel container with	44' 55/8"	7' 85/8"	8' 101/4"	7' 81/8"	8' 61/4"	71,650	10,362	61,288	3,037
corrugated walls						32,500	5,050	27,450	86.0
						71,650	11,133	60,517	3,037

Hapag-Lloyd serial number excerpt				
HLXU	901100-901599			
HLXU	900000-900199			