

- Specially designed for
  - over-height cargo
  - heavy loads
  - loading from top side, e.g. by crane
  - loading from door side, e.g. with cargo hanging from overhead tackle
- Floor height 170 mm (ground level to interior floor surface, tolerance deviation possible)
- Door header can be swung out on all open top containers
- Lashing devices have a permissible load of 1,000 kg (2,205 lbs) each

For dimensions of roof and door openings, please see page 30

	Inside dimensions					Capacity		
8' 6" high	Length	Width	Height Side		Max.	Tare	Max.	
	mm	mm	Middle mm	Side mm	gross kg	kg	payload kg	m <sup>3</sup>
	ft	ft	ft	ft	lbs	lbs	lbs	ft <sup>3</sup>
Wooden floor	12,030	2,350	2,377	2,347	30,480	3,850	26,630	66.4
Steel container with corrugated	39' 55/8"	7' 81/2"	7' 91/2"	7' 83/8"	67,196	8,488	58,708	2,345
walls and removable tarpaulin	12,029		2,380	2,346	32,500	4,050	28,450	66.5
	39' 5½"		7' 95/8"	7' 83/8"	71,650	8,929	62,721	2,348

Hapag-Lloyd serial number excerpt					
HLXU	461670-461819				
HLXU	560300-566699				

	Inside dimensions			Weights			Capacity	
8' 6" high	Length	Width	Height		Max. Tare Max.			
			Middle	Side	gross		payload	
	mm	mm	mm	mm	kg	kg	kg	m <sup>3</sup>
	ft	ft	ft	ft	lbs	lbs	lbs	ft <sup>3</sup>
Steel floor	12,029	2,350	2,380	2,344	32,500	4,000	28,500	66.3
Steel container with corrugated walls and removable tarpaulin	39' 5½"	7' 8½"	7' 95/8"	7' 71/4"	71,650	8,819	62,831	2,341

_	Hapag-Lloyd serial number excerpt					
	HLBU HLBU	800000-800999 801600-802099				

For further information about the steel-floor container, please see page 32.