

- Suitable for any general cargo
- Various lashing devices with a permissible load of 1,000 kg (2,205 lbs) each on the top and bottom longitudinal rails and the corner posts
- Lashing rings on each top longitudinal rail, particularly suitable for the transport of hanging garment equipment
- Majority of containers tested and certified for ONE-DOOR-OFF OPERATION, but then with limited stack weight
- Floor height 170 mm (ground level to interior floor surface, tolerance deviation possible)

	Inside dimensions			Door openings		Weights			Capacity
8' 6" high	Length	Width	Height	Width	Height	Max. gross	Tare	Max. payload	
	mm	mm	mm	mm	mm	kg	kg	kg	m ³
	ft	ft	ft	ft	ft	lbs	lbs	lbs	ft ³
Wooden floor	12,032	2,352	2,395	2,340	2,292	32,500	3,700	28,800	67.7
Steel container with	39' 55/8"	7' 85/8"	7' 101/4"	7' 81/8"	7' 61/4"	71,650	8,157	63,493	2,391
corrugated walls							3,750	28,750	
							8,267	63,383	
	12,029	2,350	2,392			30,480	3,780	26,700	
	39' 51/2"	7' 81/2"	7' 101/8"			67,196	8,333	58,863	

Hapag-Lloyd serial number excerpt					
HLBU	124400-127699				
HLXU	536500-541499				
HLBU	112100-114899				
HLBU	151600-153899				
HLXU	439700-447168				
HLXU	448000-449999				
HLXU	502000-507749				